



# Amerex Corporation

## RUGGED

- 5 Year Manufacturer's Warranty
- Stored Pressure Design
- Polished Stainless Steel Cylinders
- All Metal Valve Construction
- Exclusive crevice free, butt welded cylinders
- Temperature Range +40°F to 120°F

## CLEAN

- Leaves no powder residue

## USER FRIENDLY

- Maximum visibility during discharge
- Large Loop Stainless Steel Pull Pin
- Bar Coded and Bi-lingual Labels



Model 240



Model 254

Model 252  
250



AVAILABLE IN A 33 GAL. FFFP WHEELED EXTINGUISHER OR STATIONARY UNIT

**Model 240** utilizes the cooling, soaking and penetrating effect of a 45-55 ft. stream of WATER. The 55 sec. discharge time makes it very effective for inexperienced operators for use on Class A fires.

**Model 254 AFFF FOAM** unique 6 liter size fills many requirements for a lighter, more compact Class A:B extinguisher. Easy and effective application with the spray nozzle. Apply to Class B liquid spills to prevent ignition. Ideal for emergency first response vehicles.

**Model 252 FFFP FOAM** adds Class B fire fighting capability to the Class A effectiveness of this extinguisher. The Alcohol Resistant fire fighting agent is effective on fires in a wide variety of Class B materials such as alcohols, polar solvents, hydrocarbons and combinations such as gasohol. Apply to a non-ignited Class B liquid spill and it will seal the surface minimizing the chance of serious fire.

**Model 250 AFFF FOAM** Class A:B extinguisher. Easy and effective application with air aspirated nozzle. Apply to Class B liquid spills to prevent ignition. Ideal for emergency first response vehicles.

**The model 240 may be freeze protected to -40°F by adding a Model 506 Anti-Freeze charge**

AGENT TYPE	WATER	AFFF FOAM		FFFP FOAM
DESIGN	HOSE & NOZZLE	HOSE & SPRAY NOZZLE		HOSE & AIR ASPIRATED NOZZLE
MODEL NUMBER	240	254	250 / 250CG	252
UL RATING	2A	2A:10B	3A:20B	3A:20B
CAPACITY	2.5 GAL	6 LITER	2.5 GAL	2.5 GAL
SHIPPING WT. (LBS. EMPTY)	7.5	7.5	11	11
HEIGHT (IN.)	24.5	19	24.5	24.5
WIDTH (IN.)	9	8	9	9
DEPTH (IN.)	7	7	7	7
RANGE (INITIAL- FT)	45-55	10-12	10-12	10-15
FM APPROVED	YES		YES	
DISCHARGE TIME (SEC.)	55	30	55	55
INCLUDED BRACKET	WALL	WALL	WALL	WALL

Manufactured and Tested to ANSI/UL Standards  
Complies with NFPA 10 Standard  
ISO-9001 / ISO-14001 Certified  
**UL LISTED**

### CONFORMS TO TEST STANDARDS:

**WATER:** CAN/ULC-S507 - ANSI/UL626 & CAN/ULC-S508 - ANSI/UL711

**FOAM:** CAN/ULC-S554 - ANSI/UL8 & CAN/ULC-S508 - ANSI/UL711

**MADE IN U.S.A.**