



Amerex Corporation

RUGGED

- 5 Year Warranty
- All Metal Valve Construction
- Rust free aluminum cylinders
- Durable High Gloss Polyester Powder Paint
- Temperature Range -22°F to 120°F

USER FRIENDLY

- Meets Many Hospital Medical Equipment Requirements
- Large Loop Stainless Steel Pull Pin
- Model 322NM Independently Tested and Approved for use in MRI Facilities to 7 Tesla
- Model 322NM Has Sanitary White Paint Finish (easy to clean)
- Bar Coded and Bi-lingual Labels

OPTION

- USCG Approved with Bracket Listed on UL Label



| MODELS | |
|--------|-----|
| 322 | 330 |
| 331 | 332 |



Also available in 50 / 100 lb. wheeled extinguishers and 100 lb. stationary.

**Model 322NM
NONMAGNETIC
MRI SAFE TO 7 TESLA**
(USES 17737 WALL HANGER - INCLUDED)



CARBON DIOXIDE is discharged as a white cloud of “snow” which smothers a fire by eliminating oxygen. It is effective for Class B flammable liquids and is electrically non-conductive. Carbon Dioxide is a clean, non-contaminating, odorless gas.

Nonmagnetic model available (Model 322NM - tested to 7 Tesla)

| AGENT TYPE | CARBON DIOXIDE | | | | |
|-----------------------|---------------------|---------|-------------|-------|-------|
| VALVE TYPE | CHROME PLATED BRASS | | | | |
| DESIGN | HORN | | HOSE & HORN | | |
| MODEL NUMBER | 322 | 322NM | 330 | 331 | 332 |
| UL RATING | 5B:C | 5B:C | 10B:C | 10B:C | 10B:C |
| CAPACITY (LBS.) | 5 | 5 | 10 | 15 | 20 |
| SHIPPING WT. (LBS.) | 14 | 14 | 28.25 | 37.75 | 50.75 |
| HEIGHT (IN.) | 17.75 | 17.75 | 24 | 30 | 30 |
| WIDTH (IN.) | 8.25 | 8.25 | 12 | 12 | 13 |
| DEPTH (IN.) | 5.25 | 5.25 | 7 | 7 | 8 |
| RANGE (INITIAL- FT) | 3-8 | 3-8 | 3-8 | 3-8 | 3-8 |
| DISCHARGE TIME (SEC.) | 10 | 10 | 10 | 12.5 | 19 |
| FM APPROVED | YES | YES | YES | YES | YES |
| INCLUDED BRACKET | WALL | NM WALL | WALL | WALL | WALL |

**Manufactured and Tested to ANSI/UL Standards
Complies with NFPA 10 Standard
ISO-9001 / ISO-14001 Certified
UL LISTED**

CONFORMS TO TEST STANDARDS:

CAN/ULC-S503 - ANSI/UL154 &
CAN/ULC-S508 - ANSI/UL711

MADE IN U.S.A.